Feature:


- Compliant with the EN54-24 standards
- PA (Public Address) system Bi-directional sound projector with transformer
- Ideal for outdoor music and speech use in school, office, hotel and airport
- Bi-directional sound projector for both sides sound dispersion
- 2×6.5" PP full range waterproof woofer
- Rated power output 5W-10W-20W at 100V
- Waterproof level of IP66
- Ceramic connector, 95°C fire-resistant cable and thermal fuse
- Line input 100V or 70V by cable tail with waterproof gland
- Aluminum enclosure and stainless metal bracket in white
- Quick installation by supplied stainless mounting bracket




Specification:

Model	PJSK-20ADEN
Description	EN54-24 Bi-Directional Sound Projector
Rated Power Output	5W-10W-20W
Speaker	2×6.5" PP full range waterproof woofer
Line Input	100V or 70V
Frequency Response	110-15KHz
SPL(@1W/m)	92dB
IP Rate	IP66
Connector	By speaker cable tail with waterproof gland
Dimension	Φ170×252mm
Material	Aluminum enclosure and stainless metal bracket in white
Mounting Way	Quick installation by supplied stainless mounting bracket
Weight	2.8kg

Side View & Dimension:





Frequency VS SPL Diagrams:

 CLIO
 FREMONIENCY
 RESPONSE

 120
 100
 100
 100

 100
 0
 0
 0
 0

 100
 0
 0
 0
 0
 0

 100
 0
 0
 0
 0
 0
 0

 100
 0
 0
 0
 0
 0
 0
 0

 100
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0

