



Feature:

- Compact mini size public address amplifier
- Rate power output at 30W & 60W
- Speaker output of 100V or 70V & 4 Ohm-8 Ohm-16 Ohm
- LED indicators for power, clip, protect and output level meters
- Mic1-2 inputs and Aux input on front panel
- Volume control for Mic1-2, Aux, bass/treble and master
- Complete amplifier protection includes short-circuit, clip, overload and high temp
- 230V AC & 24V DC both power supply system

Specification:

Model	CA-30	CA-60
Description	Compact Mixer Amplifier	
Rated Power Output	30W	60W
Speaker Outputs	100V or 70V & 4 Ohm-8 Ohm-16 Ohm	
Connector	Mic1 input by unbalanced 6.3mm phone jack Mic2 input by unbalanced 6.3mm phone jack Aux input by unbalanced 6.3mm phone jack	
Input	MIC1-2: 5-8mV, 600Ω; Aux, 150-470mV, 10KΩ, unbalanced	
Frequency Response	60Hz-15kHz(±3dB)	
S/N Ratio	Line ≥ 85dB, Mic ≥ 72dB	
THD	Less than 0.5%	
Protection	Short-circuit, clip, overload and high temp protection	
Power Consumption	60W	100W
Power Supply	230V AC & 24V DC; 50-60Hz	
Dimension	320×210×90mm	
Weight	3.5kg	4.0kg

Rear Panel:

