

# PA-100KS 10 Zone Speaker Selector



## Description:

PA-100KS is 10 zone speaker selector which is used in public address system or PA system to divide one power amplifier into 10 loudspeaker zone for separate control. Every loudspeaker zone max loading is 200 watts, so total loading capacity is 2,000 watts. The 10 zone speaker selector is ideally used for multiple zone background music system and paging system.

## Feature:

- Public Address System 10 Zone Speaker Selector
- 19" rack mount type of 2U height
- Main equipment of multiple zone PA sound system
- Divide one power amplifier into 10 loudspeaker zone for separate control
- Each unit of 10 zone capacity and expandable up to 320 zones
- Each zone power loading is 200W and max 2,00W for 10 zone
- Each 10 zone with working indicator and selective buttons
- With A & B line input from amplifier
- Black finish of aluminum front panel
- Power consumption of 15W

## Specification:

Model	PA-100KS
Description	10 Zone Speaker Selector
Zone Capacity	10zone and expandable to 320 zones
Amplifier Loading	Each zone power loading is 200W and max 2,00W for 10 zone
Amplifier Input	A & B Channel inputs
Power Requirements	AC 220-240V $\pm$ 10% 50-60Hz
Power Consumption	15W
Dimension	484x350x88 mm
Weight	6.3Kg

## Rear Panel:

