

EN54-24 Ceiling Speaker FCS-46EN

Feature:

- Commercial fireproof ceiling speaker with 100V/70V transformer.
- Ideal for school, office, hotel and airport voice evacuation and PA system.
- Compliant with the EN54-24 EVAC standard.
- Ceramic connector, fire dome, 95°C fire-resistant cable and thermal fuse
- Rated power output 6 /3 /1.5 /0.75 W at 100V.
- 3" full range speaker driver unit.
- Line input 100V or 70V with transformer.
- Metal enclosure, metal grille and metal fire dome in white.
- In-ceiling quick installation by spring clip.
- Installation: remove the fire dome, wire the speaker cable and transformer tapping, fix up the fire dome.



Specification:

Model	FCS-46EN
Description	EN54-24 Ceiling Speaker
Rated Power Output	6 / 3 / 1.5 / 0.75 W
Line Input	100V or 70V
Frequency Response	100-18KHz
SPL(@1W/m)	91dB
Speaker Unit	4" full range speaker driver unit
Cutout Size	Ø 112mm
Dimension	Ø 135×113mm
Material	Metal enclosure, metal grille in white and fire dome in red
Mounting Way	In-ceiling spring clip quick installation
Weight	1.3kg

Dimension & Mounting:



Frequency Response & Impedance:

