

Outdoor Landscape Speaker GSK-30B

Feature:

- Public address (PA) system speaker with 100V transformer.
- Designed for both background music & paging system.
- Ideal for park, garden, green area and zoo.
- 6.25" PP coaxial waterproof woofer.
- Rated power output 15W-30W and Max. 60W at 100V.
- Waterproof level of IP66.
- Line input 100V or 70V by cable tail with waterproof gland.
- UV protected ABS enclosure in green.
- Easy installation in outside ground.
- Special design of 360 degree angle sound dispersion.



Description:

The GSK-30B is an outdoor landscape garden speaker built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers, thus the CMX AUDIO PA technology landscape garden speakers support more than 600 pieces per installation sound system and the transformer technology helps the amplifier to loudspeakers distance up to more than 10kms. The GSK-30B built-in 6.25" waterproof coaxial PP speaker drivers are designed of wide frequency response 120-15kHz, the multiple power taps of 30W & 15W could meet different outdoor area sound applications and ambient noise surroundings. The organic fiber glass reinforced composite enclosure of IP66 withstands of harshest abuse, heavy damage proof no color fade for many years outdoor like seashore & swimming pool use.

Specifications:

| | |
|--------------------|---|
| Model | GSK-30B |
| Description | Outdoor Landscape Speaker |
| Rated Power Output | 30W-15W |
| Speaker | 6.25" PP coaxial waterproof woofer |
| Line Input | 100V or 70V |
| Frequency Response | 120-15KHz |
| SPL(@1W/m) | 95dB |
| IP Rate | IP66 |
| Connector | By speaker cable tail with waterproof gland |
| Dimension | Ø335×380mm |
| Material | UV protected ABS enclosure in green |
| Weight | 7.0kg |

Frequency Response VS SPL Diagrams:

